

AB PROFIT HOGA AUR BHI ZYAADA



712 LPT

BS6 P2
Phase 2 Ready

✓ Safer
💡 Smarter
♻️ Greener

⚙️ Better Fuel Efficiency
💰 Lower Total Cost of Ownership

TATA TRUCKS
DESH KE TRUCKS

Technical Specifications

Models	712 LPT DCR 125 B6M5 ST & TT
Engine	4SP BS6 Phase2 TCIC engine
Engine Type	4 Cylinder in line water cooled direct Injection diesel engine with intercooler
Engine Displacement	2 956 cc
Power	92 kW (125 Ps) @ 2 800 r/min (Heavy Mode) 73.6 kW (100 Ps) @ 2800 r/min (Light Mode)
Torque	360 Nm @ 1 400 - 1 800 r/min (Heavy Mode) 300 Nm @ 1 000 - 2 200 r/min (Light Mode)
Clutch	Single plate dry friction type - 280 mm dia
Gearbox	G400 (5F, 1R), Cable Shift Mechanism
Gearbox Ratio	1st - 6.45, 2nd - 3.66, 3rd - 2.29, 4th - 1.49, 5th - 1.00, Rev - 6.26
Suspension - Front Type	Parabolic Suspension with rubber bush and Hydraulic double acting telescopic shock absorbers
Suspension - Rear Type	Semi-Elliptical Leaf Spring with Aux Springs
Tyres	Radial 8.25 R 16 Low CRR Tyre (FR-2, RR-2, Spare -1)
Front Tyre Spec	8.25R16 - 16PR Radial Low CRR Tyre
Rear Tyre Spec	8.25R16 -16PR Radial Low CRR Tyre
Cabin Type	Day Cab
Steering Type*	Tilt & Telescope Power Steering (Dia - 420 mm 2 spoke)
Brakes Type	Dual Circuit Full Air S* Cam Brakes With Auto Slack Adjuster (Drum - Drum) (Dia - 360 mm)
Ground Clearance	220 mm
Gradeability	33 % (ST) 32 % (TT)
Rear Axle	TATA RA 1109R Fully Floating Benjo Axle (RAR - 4.857)
Battery	12 V - 100 Ah
Fuel Tank Capacity	90 l, 120 l
Load Body Variants	CAB, NSD, High Deck, Container, Reefers
GVW	7 490 kg
FAW	3 640 kg
RAW	3 850 kg
Long Member Size (LxBxH)	186 mm x 60 mm x 4 mm

Wheelbase	3 550 (ST)			3 920 (TT)	
TCD	12 500 mm			13 500 mm	
Variants	CAB	NSD	HSD	CAB	HSD
Load Body Dimensions (LxWxH)	-	4 350 mm x 1 960 mm x 585 mm	4 347 mm x 2 117 mm x 1 825 mm	-	5 218 mm x 2 117 mm x 1 820 mm
Overall Dimensions (LxWxH)	6 385 mm x 2 155 mm x 2 465 mm	6 415 mm x 2 155 mm x 2 465 mm	6 485 mm x 2 255 mm x 2 920 mm	7 260 mm x 2 155 mm x 2 475 mm	7 350 mm x 2 255 mm x 2 920 mm
Seating Capacity	D+2				
DEF Tank Size	18 l				
Service Interval	1 Year or 40 000 km				
Propeller Shaft	SPL 70 with Flange Dia. 120 OD with PCD 100 mm				
Ignition Switch	With Illuminating ring				

Key Features & Benefits

Dual Mode FE Switch Light & Heavy
 Cruise Control
 THU Bearing
 Firmware Over The Air
 Warranty (Vehicle) 3 Year or 3 00 000 km

Applications

E-Commerce
 Food Grains
 Cement
 FMCG
 LPG Cylinder
 Container
 White Goods
 Fruits & Vegetables



TATA MOTORS SAMPOORNA SEVA
 TATA WARRANTY | TATA GENUINE PARTS | TATA SURAKSHA | TATA PROLIFE | TATA KAVACH | TATA ALERT
 TATA DELIGHT | TATA OK
 AAPKE SAATH HAR KADAM
 TOLL-FREE 18 00 20 97 979

TATA MOTORS

To know more, visit your nearest Tata Motors dealership

www.light-trucks.tatamotors.com

📞 18 00 20 97 979 Follow us on