

AB PROFIT HOGA AUR BHI ZYAADA



FE
Series

BS6 P2
Phase 2 Ready

- ✓ Safer
- 💡 Smarter
- 🌱 Greener
- ⚙️ Better Fuel Efficiency
- 💰 Lower Total Cost of Ownership

1012 LPT

TATA TRUCKS
DESH KE TRUCKS

Technical Specifications

Models	1012 LPT DCR 125B6PH2M5							
Engine	4SPCR BSVI Ph2							
Engine Type	4 Cylinder in line water cooled direct Injection diesel engine with intercooler							
Engine Displacement	2 956 cc							
Power	74.5 kW (100 Ps) @ 2 800 r/min (Light Mode) 92 kW (125 Ps) @ 2 800 r/min (Heavy Mode)							
Torque	360 Nm @ 1400 - 1 800 r/min (Light Mode); 300 Nm @ 1 000 - 2 200 r/min (Heavy Mode)							
Clutch	Single plate dry friction type - 310 mm dia (with Booster)							
Gearbox	G550, 5 Speed, MK2 Manual Synchromesh Gearbox (5F, 1R)							
Gearbox Ratio	1st - 8.07, 2nd - 4.76, 3rd - 2.75, 4th - 1.66, 5th - 1.00, Rev - 7.48							
Suspension - Front Type	Parabolic leaf spring with Hydraulic Double acting Telescopic Shock Absorbers							
Suspension - Rear Type	Semi elliptical leaf spring,							
Tyres	8.25 R16 - 16PR Low CRR Tyre (Front - 2 / Rear-4)							
Cabin Type	New Gen LPT Walk Through Day Cabin							
Steering Type*	Tilt & Telescopic Power Steering (Dia 420 mm) 4 Spoke							
Brakes Type	Dual Circuit Full Air S* Cam Brakes With Auto Stack Adjuster (Drum - Drum) - 325 mm							
Ground Clearance	214 mm							
Gradeability	22.90 %							
Rear Axle	Banjo Type - Single reduction hypoid gears, fully floating axle shafts - RAR: 4.857							
Battery	12V, 100 Ah							
Fuel Tank Capacity	120 l HD Polymer Fuel Tank							
Load Body Variants	CAB & HSD							
GVW	10 500 kg							
FAW	3 450 kg							
RAW	7 050 kg							
Long member Size (Lx B x H)	200 mm x 60 mm x 5 mm							
Wheelbase	3 550 mm	3 920 mm	4 530 mm	4 920 mm				
TCD	12 500 mm	13 800 mm	16 100 mm	17 500 mm				
Variants	CAB	HSD	CAB	HSD	CAB	HSD	CAB	HSD
Load Body Dimensions (L x W x H)	NA	4 347 mm x 2 260 mm x 2 090 mm	NA	5 340 mm x 2 260 mm x 2 090 mm	NA	6 290 mm x 2 260 mm x 2 090 mm	NA	6 915 mm x 2 260 mm x 2 090 mm
Warranty	3 years or 3 00 000 km							
Seating Capacity	D + 2							
DEF Tank Size	18 l							
FIP Model	Delphi CR System (1 800 + bar pressure)							
Service Interval	40 000 km or 1 Year. Hub Greasing 1 20 000 km, Gear Oil Change Interval - 2 40 000 km							

Key Features & Benefits

- Gear Shift Advisor
- 2 200 mm Wide Cabin
- Dual Mode FE Switch Light & Heavy
- THU Bearing
- Low CRR Tyre
- Fleetedge Telematics

Applications



TATA MOTORS

To know more, visit your nearest Tata Motors dealership

www.light-trucks.tatamotors.com

📞 18 00 20 97 979 Follow us on